



#### TRANSPORT

Very easy to carry.  
Folding legs under the frame

#### EXTENSION SIDE TABLE

Very practical when cutting big tile sizes.  
(Optional: Art 85015)

#### PACKAGING

Multilingual flexographed packaging

# VIP

## RADIAL TILE SAWS



### Art. 845

### Art. 850

### Art. 855


DIAMOND DISK	ø200 mm. c/c standard	ø200 mm. c/c standard	ø200 mm. c/c standard
ENGINE	230V   50Hz   1,3Hp/1,0kW	230V   50Hz   1,3Hp/1,0kW	230V   50Hz   1,3Hp/1,0kW
ROTATION SPEED	2800 rpm.	2800 rpm.	2800 rpm.
MAX CUTTING LENGTH	500 mm.	650 mm.	950 mm.
MAX CUTTING DEPTH AT 90°	40 mm.	40 mm.	40 mm.
MAX CUTTING DEPTH AT 45°	40 mm.	40 mm.	40 mm.
MAX SIZE TILE FOR DIAGONAL CUT	354 x 354 mm.	460 x 460 mm.	672 x 672 mm.
WORKING TABLE DIMENSIONS	445 x 403 mm.	600 x 403 mm.	915 x 403 mm.
WATER RECYCLING PUMP TYPE	S0 standard	S0 standard	S0 standard
DIMENSION MACHINE IN SERVICE	1010x440x h. 1250 mm.	1160x440x h. 1250 mm.	1460x440x h. 1250 mm.
DIMENSION MACHINE IN STOCK	960x570x h. 500 mm.	960x570x h. 500 mm.	1270x570x h. 500 mm.
DIMENSION 8 MACHINES ON PALLET	1000x1140x h. 2100 mm.	1000x1140x h. 2100 mm.	1140x1270x h. 2100 mm.
NET WEIGHT	31 Kg.	34 Kg.	39 Kg.

*Designed  
and made  
in Italy*



**BATTIPAV**<sup>TM</sup>  
MACCHINE PER EDILIZIA | MACHINES FOR BUILDING


AUTHORIZED DEALER:




Z. i. 2 - Via Cavatorta, 6/1 | 48010 Cotignola (Ra) | ITALY  
Tel. +39 0545 40004 | Fax +39 0545 41724  
www.nuova-battipav.com | sales@nuova-battipav.com

January 2011

**APPLICATION**  
Built to cut ceramic tiles, porcelain  
stoneware and marble



**45° CUT**  
Position 45° angle cuts.



**CARRIAGE ENGINE GROUP**  
The carriage engine group slides with 6 ball-bearings (of which 2 are adjustable) on the track. The sliding is very fast and precise.




**PIVOTING HEAD**  
Tilting cutting head for one greater rapidity and precision in the execution of particular cuts. It can be locked at the wished height.



**CUTS IN SERIES**  
Execution of the cuts in series due to the blocking handle with the immediate reading of the length on the rail.



Easy to clean.



**Spray system**  
DISK'S LUBRICATION



ORIGINAL RECYCLING PUMP