

## Technical data

	IVUR 40	IVUR 50	IVUR 58
<b>Weight</b>			
Operating weight CECE (in kg)	14	16	17
Effective diameter approx. mm	400	500	600
<b>Dimensions</b>			
Vibrator diameter mm	40	50	58
Vibrator length mm	330	370	420
Protective tube length mm	5000	5000	5000
Weight kg	7.5	9.5	10.5
<b>Connection vibrator section</b>			
Input voltage (V)	220	220	220
Rated current (A)	1.8	2.6	3
Frequency (Hz)	200	200	200
Rated power (W)	650	850	1050
<b>Connection converter section</b>			
Voltage (V)	230	230	230
Frequency (Hz)	50	50	50
Rated current (A)	4.6	4.6	4.6
Rated power (kVA)	1.6	1.6	1.6
Connecting cable (m)	10	10	10
<b>Degree of protection</b>	IP 67	IP 67	IP 67

	IVUR 40	IVUR 50	IVUR 58
<b>Noise and vibration values</b>			
Sound pressure level LPA (at the operating station in accordance with 2000/14/EC, in dB(A))	72	78	81
Hand/arm vibration (effective weighted value of the acceleration on the guide handle, determined in accordance with 2006/42/EC, Part 1, in m/s <sup>2</sup> )	0.7	2.2	2.7